SUPER 104

104" WIDTH OF CUT MAKES BIG JOBS EASY



ZERO-TURN MANEUVERABILITY

Hustler's Super 104 can easily handle acres of work. Offering a 104" width of cut, zero-turn precision and up to an impressive 11 mph speed, this machine is in a class by itself. Its industrial-grade HyperDrive® Hydro System is engineered to handle thousands of hours of the toughest jobs out there. Transporting is easy as it folds into an 80" transport width. A Grammar suspension seat, welded steel deck and 12 gallon fuel capacity provide comfort, durability and more performance than your average zero-turn mower.



HYPERDRIVE® HYDRO SYSTEM

Features industrial-grade pumps and motors to handle tough jobs and long days in stride.



104" WIDTH OF CUT

Widest and most productive commercial zero-turn available



80" TRANSPORT WIDTH

Fits most trailers making it easy to transport from job-to-job.

LIFETIME WARRANTY











ENGINE

Manufacturer Vanguard

HP 36HP - Vanguard BIG BLOCK™

37HP - Vanguard BIG BLOCK™ EFI

(Per SAE J1995)

Displacement 993 cc
Cooling Air cooled

Air Cleaner Heavy duty canister
Engine Warranty 5 year (Vanguard only)

DRIVE SYSTEM

Type Dual hydrostatic
Pumps Danfoss DDC20
Wheel Motors Parker TG0360

Hydraulic Lines Stainless steel Parker seal loc technology

Reservoir Capacity 3 gallons

Speed Up to 11 mph

Parking Brakes Patented automatic

DECKS

Cutting Width Rear discharge: 104"

Cutting Heights 1"- 5.5"

Deck Lift Hydraulic powered

Depth 5.5" Blades 5

Blade Length 1 - 23.86" x 2.50" x .20" CW 1 - 23.86" x 2.50" x .20" CCW

1 - 20.50" x 2.50" x .20" CCW 2 - 20.50" x 2.50" x .20" CW

Spindles Ductile cast iron with steel shafts and

sealed ball bearings

Deck Belts 1 per deck

Drive Electric PTO clutch

Construction 11 ga. welded steel

Spindle Mounts Reinforced 7 ga. doubler

Impact/Trim Areas 1.5" x .375" steel bar protector

CONSTRUCTION

Frame 1.5" x 3.0" x .188" steel

Front Caster Wheels Mounted tapered greasable bearings

Front Caster Forks Fabricated 1/2" steel

GENERAL

Seat Grammer suspension seat, isolator platform

Fuel Capacity 12 gallons Cup Holder Yes

Front Tire 15 x 6.0 - 6
Drive Tire 26 x 12 - 12

DIMENSIONS

Weight 2500 lbs
Height w/rops up 71.5"
Height w/rops Folded 54"
Length 95.5"

Width 106.1" wings down

80.0" wings up at gauge wheels 72.5" wings up at deck base

Tire Width 60.3"

PRODUCTIVITY*

Acres Per Hour 9.24

OPTIONAL ACCESSORIES

Mulch kit

Steering lever extension kit Light kit Anti-scalp kit

Flasher kit Beacon kit Flex Forks® Hitch kit

SUPER 104 | AT A GLANCE

- Widest and most productive commercial zero-turn available
- Heavy-duty fabricated frame unmatched durability
- Exclusive SmoothTrak™ steering responsive, precise control
- Patented automatic park brake
- Wide area mower with 80" transport width fits most trailers
- Up to 11 mph speed
- 12 gallon fuel capacity
- · Hydraulic powered deck height adjustment
- Grammer suspension seat with isolator platform
- HyperDrive® industrial hydro system mow in tough conditions without losing performance

^{*} Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

^{**} Specifications are subject to change without notice.