


ZT3500 Zero-Turn Mower



Designed for big jobs and mowing larger areas, the ZT3500 zero-turn, ride-on mower is built with productivity, operator comfort, and easy maintenance in mind. With a rigid steel frame, 23-inch drive tires, superior hydrostatic transmission, and a high-back, full-mechanical suspension seat, you can get the job done faster and with less fatigue.

[Request a Quote](#)

[Schedule a Demo](#)

[Find a Dealer](#)

ZT3500 Specifications

| Key Specifications | | | |
|---------------------------|------------------------|------------------------|--|
| ZT3500 - 48" | ZT3500 - 61" | ZT3500 - 52" | |
| Engine Power | | | |
| 17.9 kW | 17.9 kW | 17.9 kW | |
| Cutting Deck Width | | | |
| 1219 mm | 1549 mm | 1320 mm | |
| Ground Speed | | | |
| 16 km/h | 16 km/h | 16 km/h | |
| Drive Wheel Size | | | |
| 13 x 6.5-6 | 13 x 6.5-6 | 13 x 6.5-6 | |
| Engine | | | |
| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" | |
| Model | | | |
| Kaw FT730V | Kaw FT730V | Kaw FT730V | |
| Engine power | | | |
| 17.90 kW | 17.90 kW | 17.90 kW | |
| Displacement | | | |
| 726.00 cm ³ | 726.00 cm ³ | 726.00 cm ³ | |
| Fuel Capacity | | | |
| 29.50 L | 29.50 L | 29.50 L | |
| Air Filter | | | |
| Dual-Stage Canister | Dual-Stage Canister | Dual-Stage Canister | |
| Electrical | | | |
| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" | |
| Charging System | | | |
| 15.00 A | 15.00 A | 15.00 A | |
| Clutch | | | |

| | | |
|----------|----------|----------|
| 169.00 N | 169.00 N | 169.00 N |
|----------|----------|----------|

Deck

| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" |
|--------------|--------------|--------------|
|--------------|--------------|--------------|

Mower Deck

| | | |
|----------------------------|----------------------------|----------------------------|
| TufDeck Pro Cutting System | TufDeck Pro Cutting System | TufDeck Pro Cutting System |
|----------------------------|----------------------------|----------------------------|

Width

| | | |
|------------|------------|------------|
| 1219.00 mm | 1320.00 mm | 1549.00 mm |
|------------|------------|------------|

Adjustable Anti-Scalp Rollers

| | | |
|-----|-----|-----|
| 3.0 | 3.0 | 7.0 |
|-----|-----|-----|

Cutting Height

| | | |
|---------------|---------------|---------------|
| 38.0-114.0 mm | 38.0-114.0 mm | 38.0-114.0 mm |
|---------------|---------------|---------------|

Blade Tip Speed

| | | |
|----------------------------|----------------------------|----------------------------|
| 73.6 mps @ 3500 Engine rpm | 81.5 mps @ 3550 Engine rpm | 85.4 mps @ 3500 Engine rpm |
|----------------------------|----------------------------|----------------------------|

Discharge Chute

| | | |
|-------------------------|-------------------------|-------------------------|
| Flexible Molded Polymer | Flexible Molded Polymer | Flexible Molded Polymer |
|-------------------------|-------------------------|-------------------------|

Frame

| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" |
|--------------|--------------|--------------|
|--------------|--------------|--------------|

Front and Rear

| | | |
|---|---|---|
| 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame | 1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame |
|---|---|---|

Machine Length

| | | |
|------------|------------|------------|
| 1930.00 mm | 1930.00 mm | 2006.00 mm |
|------------|------------|------------|

Machine Weight

| | | |
|-----------|-----------|-----------|
| 400.00 kg | 407.00 kg | 422.00 kg |
|-----------|-----------|-----------|

Transmission

| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" |
|--------------|--------------|--------------|
|--------------|--------------|--------------|

Type

| | | |
|-----------------------------------|-----------------------------------|-----------------------------------|
| HG ZT-3400 Hydrostatic Transaxles | HG ZT-3400 Hydrostatic Transaxles | HG ZT-3400 Hydrostatic Transaxles |
|-----------------------------------|-----------------------------------|-----------------------------------|

Pump Displacement

| | | |
|-----------------------|-----------------------|-----------------------|
| 12.00 cm ³ | 12.00 cm ³ | 12.00 cm ³ |
|-----------------------|-----------------------|-----------------------|

Oil Capacity

| | | |
|--------|--------|--------|
| 4.00 L | 4.00 L | 3.80 L |
|--------|--------|--------|

Forward Speed

| | | |
|------------|------------|------------|
| 16.00 km/h | 16.00 km/h | 16.00 km/h |
|------------|------------|------------|

Reverse Speed

| | | |
|-----------|-----------|-----------|
| 5.60 km/h | 5.60 km/h | 5.60 km/h |
|-----------|-----------|-----------|

Wheels

| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" |
|--------------|--------------|--------------|
|--------------|--------------|--------------|

Drive Wheel Size

| | | |
|--------------|--------------|--------------|
| 23 x 10.5-12 | 23 x 10.5-12 | 23 x 10.5-12 |
|--------------|--------------|--------------|

Front Caster Wheel Size

| | | |
|------------|------------|------------|
| 13 x 6.5-6 | 13 x 6.5-6 | 13 x 6.5-6 |
|------------|------------|------------|

Caster Arm Attachment

| | | |
|-----------------|-----------------|-----------------|
| Welded to Frame | Welded to Frame | Welded to Frame |
|-----------------|-----------------|-----------------|

Seat

| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" |
|--------------|--------------|--------------|
|--------------|--------------|--------------|

Description

| | | |
|--|---|--|
| High Back, Full Mechanical Suspension Seat | High-Back, EVC and Spring Suspension Seat | High Back, Full Mechanical Suspension Seat |
|--|---|--|

Fore-Aft Adjustment

| | | |
|------------------|------------------|------------------|
| Seat Slide Lever | Seat Slide Lever | Seat Slide Lever |
|------------------|------------------|------------------|

Dimensions

| ZT3500 - 48" | ZT3500 - 52" | ZT3500 - 61" |
|--------------|--------------|--------------|
|--------------|--------------|--------------|

Height (ROP's Up)

| | | |
|------------|------------|------------|
| 1733.00 mm | 1733.00 mm | 1733.00 mm |
|------------|------------|------------|

Height (ROP's Down)

| | | |
|------------|------------|------------|
| 1190.00 mm | 1190.00 mm | 1190.00 mm |
|------------|------------|------------|

| Overall Length | | |
|----------------------------|-------------|-------------|
| 1930.00 mm | 1930.00 mm | 1930.00 mm |
| Overall Width (Chute Up) | | |
| 1241.00 mm | 1381.00 mm | 1600.00 mm |
| Overall Width (Chute Down) | | |
| 1591.00 mm | 1731.00 mm | 1950.00 mm |
| Cutting Height | | |
| 38 - 114 mm | 38 - 124 mm | 38 - 114 mm |
| Wheelbase | | |
| 1220.00 mm | 1220.00 mm | 1220.00 mm |
| Cutting Width | | |
| 1220.00 mm | 1321.00 mm | 1550.00 mm |
| Blade Length | | |
| 413.00 mm | 457.00 mm | 533.00 mm |

ZT3500 Features

Expand all ▾

▾ Performance ⁴

▾ Comfort ¹

▾ Built for your needs ¹

▾ Serviceability ¹

▾ Durability ¹

Similar Machines



WB700 Zero-Turn Walk-Behind Mower

Walk-behind, mower with high stability in uneven terrain, powerful hydraulic drive, and a proven engine.

[Learn More >](#)



ZT2000 Zero-Turn Mower

The Bobcat ZT2000 is an efficient zero-turn mower that offers unmatched durability and delivers a professional-quality cut.

[Learn More >](#)



ZT3000 Zero-Turn Mower

Ride-on, zero-turn mower with a robust steel-tubed frame.

[Learn More >](#)

